

SITE DATA - ABINGDON:

TOTAL SITE AREA: 6.96 AC.
EXIST. PUBLIC RW: 0.65 AC.
AREA OUTSIDE PUBLIC RW: 6.31 AC.

PROP. DENSITY: 3.88 DU / AC.
MAX. ALLOWABLE LOTS: 27
PROPOSED LOTS: 23

EXIST. PUBLIC RW: 0.65 AC.
PROP. AREA IN LOTS: 3.01 AC.
PROP. AREA IN RW: 1.03 AC.
PROP. COMMON OPEN SPACE: 2.27 AC.
PROP. LINEAR FEET OF STREET: 877 LF

SETBACKS:

MIN. FRONT YARD: 17 FT FROM RW
MIN. GARAGE: 20 FT FROM BACK OF SIDEWALK
MIN. SIDE YARD: 5 FT
MIN. SIDE YARD AT CORNER: 10 FT
MIN. REAR YARD: 30 FT

LOTS:

MIN. LOT WIDTH REQUIRED: 40 FT (AT FRONT SETBACK)
MIN. LOT WIDTH PROVIDED: 40 FT
MIN. LOT AREA PROVIDED: 4,500 SF
AVG. LOT AREA PROVIDED: 5,700 SF
MAXIMUM BUILDING HEIGHT: 35 FT

TREE SAVE:

REQUIRED MINIMUM TREE SAVE AREA:
TOTAL AREA = 6.96 AC
EXIST. PUBLIC RW = 0.65 AC
EXIST. RECORDED UTILITY ESMT. = 0.34 AC
NET AREA FOR TREE SAVE CALCULATION = 5.97
TREE SAVE AREA REQUIRED = 5.97 AC. X 10%
= 0.59 AC
TREE SAVE AREA PROVIDED = 0.61 AC.

NATURAL AREA:

REQUIRED MINIMUM NATURAL AREA:
TOTAL AREA = 6.96 AC
EXIST. PUBLIC RW = 0.65 AC
NET AREA FOR NATURAL AREA CALCULATION = 6.31
NATURAL AREA REQUIRED = 6.31 AC. X 17.5%
= 1.10 AC.

UNDISTURBED NATURAL AREA: 0.61 AC. @ 100% = 0.61 AC.
REVEGETATED NATURAL AREA: 0.35 AC. @ 100% = 0.35 AC.
NATURAL AREA IN PLANTING STRIP: 0.19 AC. @ 75% = 0.14 AC.
NATURAL AREA PROVIDED = 1.10 AC.

COMMON OPEN SPACE:

REQUIRED MINIMUM COMMON OPEN SPACE:
TOTAL AREA = 6.96 AC
EXIST. PUBLIC RW = 0.65 AC
NET AREA FOR C.O.S. AREA CALCULATION = 6.31
C.O.S. AREA REQUIRED = 6.31 AC. X 10%
= .63 AC.



Know what's below.
Call before you dig.

DEVELOPMENT INFORMATION:

NAME: ABINGDON (A.K.A. - CLAWSON TRACT)
DEVELOPER: PULTE HOME CORP.
BRETT MANERY
11121 CARMEL COMMONS BLVD.
SUITE 400
CHARLOTTE, NC 28226
ENGINEER: ESP ASSOCIATES, P.A.
DANIS SIMMONS, PE
P.O. BOX 7030
CHARLOTTE, NC 28241
PROPERTY OWNERS: CLAWSON, VAN B. JR.
DB 01140, PG. 367
TAX PARCEL ID# 22902116
9600 WADE ARDREY RD
ARDREY, W.M.
DB 01140, PG. 164
TAX PARCEL ID# 22902102
9700 WADE ARDREY RD
EXISTING: R-6 (CD)
REZONING PETITION 2012-070

CENTERLINE LINE TABLE

LINE	LENGTH	BEARING
L1	61.57'	N 65°12'12" W
L2	127.43'	S 67°17'43" W
L3	430.34'	N 89°02'53" W
L4	23.13'	N 22°42'17" W
L5	80.28'	N 14°43'50" E
L6	37.02'	N 1°58'26" E
L7	13.07'	N 2°13'01" W
L8	103.59'	N 2°01'52" W


STREET CENTERLINE CURVE TABLE

CURVE	RADIUS	LENGTH	TANGENT	CHORD	BEARING	DELTA
C1	200.00'	165.81'	88.01'	161.10'	N 88°57'15" W	47°30'06"
C2	150.00'	61.93'	31.41'	61.49'	S 79°07'25" W	23°39'25"
C3	200.00'	130.67'	67.77'	128.36'	N 3°59'14" W	37°28'06"
C4	150.00'	33.40'	16.77'	33.33'	N 8°21'08" E	12°45'24"
C5	150.00'	10.97'	5.49'	10.97'	N 0°07'18" W	4°11'27"

LEGEND

	EXIST. SIDEWALK
	PROP. REVERSE FRONTAGE BUFFER
	LAND TREE SAVE AREAS
	REVEGETATED NATURAL AREAS
	PROP. SIDEWALK
	PROP. SIGHT TRIANGLE
	PROP. STORM DRAINAGE EASEMENT (SDE)
	PROP. SANITARY SEWER EASEMENT
	PROP. SIDEWALK EASEMENT
	PROP. COMMON OPEN SPACE AREA
	EXIST. WETLANDS

GRAPHIC SCALE



SITE NOTES

- ALL RADI DIMENSIONS SHOWN ARE TO BACK OF CURB, UNLESS OTHERWISE NOTED.
- SHADED CURB & GUTTER INDICATES LOCATION FOR SPILL CURB.
- MINIMUM CROSS SLOPE ON ALL ASPHALT TO BE 3/8" PER FOOT.
- MINIMUM SLOPE ON CURB AND GUTTER SHALL BE 0.50%, UNLESS SPILL CURB IS INDICATED.
- ALL HANDICAP ACCESS RAMP SHALL COMPLY WITH THE LATEST EDITION OF THE ADA ACCESSIBILITY GUIDELINES.
- SIGHT TRIANGLES SHOWN ARE THE MINIMUM REQUIRED.
- NO OBSTRUCTIONS, PLANTINGS, OR FENCING SHALL BE PERMITTED WITHIN SIGHT TRIANGLES, STORM DRAINAGE EASEMENTS (SDE) AND SANITARY SEWER EASEMENTS.
- ALL SITE CONCRETE (SIDEWALKS, CURB & GUTTER, ETC.) SHALL NOT BE LESS THAN 3600 PSI STRENGTH AT 28 DAYS.
- LIGHTING PLAN TO BE DESIGNED BY OTHERS.
- IRRIGATION PLAN TO BE DESIGNED BY OTHERS.
- PROPOSED TREE SAVE AREA(S) LOCATED WITHIN VEHICULAR SIGHT DISTANCE LINES ARE SUBJECT TO REVIEW AND APPROVAL BY CDOT. IT IS THE PETITIONER'S INTENT TO "LIMB UP" TREES IN THESE AREA(S) IN ORDER TO PROVIDE VEHICULAR SIGHT DISTANCE TO MEET REQUIREMENTS ESTABLISHED BY CDOT. SUBJECT TO CDOT AND URBAN FORESTRY REVIEW AND APPROVAL. SOME TREES LOCATED WITHIN PROPOSED VEHICULAR SIGHT DISTANCE LINES MAY NEED TO BE REMOVED. SHOULD TREES WITHIN THE PROPOSED TREE SAVE AREAS HAVE TO BE REMOVED TO MEET VEHICULAR SIGHT DISTANCE REQUIREMENTS, THESE AREAS WILL NOT BE SUBJECT TO TREE SAVE REQUIREMENTS.

N/F
ROCK, DALIA HERRERO - TRUSTEE
ROCK, DAMIAN WHITNEY -
PERSONAL RESIDENCE TRUST OF
DB 25420 PG 418
TAX PARCEL ID #22902101

0.04 AC. OF WETLANDS TEMPORARILY
IMPACTED AND RE-PLANTED IN THIS
AREA PER USACE ACTION ID
#2013-00924 AND NCDEM APPROVAL
OF 401 WATER QUALITY
CERTIFICATION. DWG #13-0792

END OF PROP. 2'-6"
STD. CURB & GUTTER

END OF PROP. 6"
SIDEWALK

EXIST. EDGE OF
PAVEMENT (TYP.)

EXIST. PAVEMENT
STRIPING (TYP.)

END OF EXIST. 2'-6"
STD. CURB & GUTTER

EXIST. EDGE OF
PAVEMENT (TYP.)

EXIST. PAVEMENT
STRIPING (TYP.)

SITE BENCHMARK
NAIL IN POWER POLE
ELEV. 613.44'

APPROVED FOR
CONSTRUCTION
CHARLOTTE-MECKLENBURG PLANNING DEPARTMENT
By: Joshua Weaver 4-25-2014

BOUNDARY LINE TABLE			
LINE	LENGTH	BEARING	
L9	542.73'	S 75°06'17" E	
L10	654.76'	N 71°17'19" E	
L11	30.05'	N 71°17'19" E	
L12	157.96'	N 86°01'46" W	
L13	63.27'	N 85°47'10" W	
L14	277.62'	S 23°45'05" W	
L15	167.29'	S 23°45'05" W	
L16	30.34'	S 75°06'17" E	

BOUNDARY CURVE TABLE						
CURVE	RADIUS	LENGTH	TANGENT	CHORD	BEARING	DELTA
C6	254.50'	176.68'	92.07'	173.15'	S 74°19'34" W	39°46'33"
C7	236.10'	120.67'	61.68'	119.36'	S 38°22'38" W	29°17'02"

ESP Associates, P.A.
P.O. Box 7030
Charlotte, NC 28241
3475 Lameron Blvd.
Fort Mill, SC 29708
704-583-9949 (NC)
803-502-2440 (SC)
www.espassociates.com

NORTH CAROLINA
LICENSE NO.:
C-0587
ESP ASSOCIATES, P.A.

NORTH CAROLINA
PROFESSIONAL
SEAL
ENGINEER
DANIS SIMMONS
025775

BY	DATE	REVISION	REVISION PER 1ST SUBMITTAL COMMENTS	REVISION PER 2ND SUBMITTAL COMMENTS	REVISION PER CITY COMMENTS
BCL	11/06/13	1			
BCL	02/28/14	2			
BCL	03/28/14	3			

SITE PLAN

ABINGDON

PULTE HOME CORP.

CITY OF CHARLOTTE, NC

PROJECT INFORMATION

PROJECT MANAGER: MRR

DESIGNED BY: BCL

DRAWN BY: BCL

PROJECT NUMBER: AU09.400

ORIGINAL DATE: 5/30/2013

SHEET: C3.0