

GENERAL NOTES:

- I. ALL PLANTS SHALL MEET OR EXCEED THE MINIMUM STANDARDS SET BY THE U.S.D.A. STANDARD FOR NURSERY STOCK SPONSORED BY THE AMERICAN ASSOCIATION OF
- NURSERYMEN, INC., WASHINGTON, D.C. 2. CONTRACTOR TO REVIEW PLANT SELECTION WITH LANDSCAPE ARCHITECT PRIOR TO INSTALLATION AND DURING PROPOSAL PREPARATION FOR QUALITY CONTROL AND
- 3. LANDSCAPE CONTRACTOR SHALL VERIFY UTILITY AND STORM DRAINAGE LOCATION IN THE FIELD, PRIOR TO BEGINNING CONSTRUCTION.
- 4. ADJUST TREE PLANTING LOCATIONS TO AVOID UNDERGROUND UTILITIES--PLANT 15-20' OFF SEWER AND STORM DRAINAGE LINES; 10-15' OFF GAS, WATER, PHONE AND
- UNDERGROUND ELECTRICAL LINES. 5. ANY CONFLICT BETWEEN TREES AND UTILITIES SHALL BE RESOLVED IN THE FIELD WITH
- FINAL TREE LOCATIONS APPROVED BY THE LANDSCAPE ARCHITECT 6. ! ARGE MATURING TREES MUST BE A MINIMUM 25 TO 30 FEET FROM THE OVERHEAD DISTRIBUTION OR TRANSMISSION LINES. IF TREES CONFLICT WITH POWER LINES OR
- SIGNS, CALL URBAN FORESTER TO RESOLVE BEFORE PLANTING. 7. PLEASE CALL 336-4255 FOR AN INSPECTION OF TREE PROTECTION AND/ OR TREE FLANTING AREAS, 7 TO 10 DAYS BEFORE THE TEMPORARY OR FINAL CERTIFICATE OF
- 8. ATTENTION CONTRACTOR/LANDSCAPER: IT IS THE RESPONSIBILITY OF THE CONTRACTOR/LANDSCAPER TO NOTIFY THE URBAN FORESTER OF ANY SITE CONFLICTS THAT AFFECT TREE SPECIES OR LOCATIONS PRIOR TO PLANTING TREES. CALL 336-3599 OR THE URBAN FORESTER NAMED ON THE APPROVED PLAN FOR ANY CONFLICTS REGARDING SIGHT, SIGNS, OVERHEAD POWERLINES OR OTHER UTILITIES.
- VIOLATIONS OF TREE PROTECTION REQUIREMENTS ARE SUBJECT TO FINES AND/ OR MEDIATE CORRECTIVE ACTION MITIGATION. 10. MINIMUM TREE SIZE AT PLANTING IS 2-INCH CALIPER (FOR SINGLE STEM TREES). ALL
- MULTI-STEM PLANTS MUST BE TREE FORM, MAXIMUM 3 TO 5 TRUNKS, AND MINIMUM & FEET "ALL. MITIGATION TREES ARE 3-3 1/2" CAL. II. ALL STRAPPING AND TOP 2/3 OF WIRE BASKET MUST BE CUT AWAY AND REMOVED
- BURLAP FROM ROOT BALL. 12. FOR NEW PLANTING AREAS, REMOVE ALL PAVEMENT, GRAVEL SUB-BASE AND CONSTRUCTION DEBRIS; REMOVE COMPACTED SOIL AND ADD 24" NEW TOPSOIL -OR-UNCOMPACT AND AMEND THE TOP 24" OF EXISTING SOIL TO MEET TOPSOIL/PLANTING
- TREE OR PLANTING AREA). 13. MULCH ALL PLANTING BEDS WITH 4" OF PINE NEEDLE MULCH.
- 14. APPLY PRE-EMERGEN HERBICIDE TO PLANTING BEDS PRIOR TO MULCHING. 15. SEED ALL DISTURBED AREAS EXCEPT PLANTING BEDS AS NOTED.

GENERAL TREE NOTES

TREES TO BE 40% 2" cal. LARGE MATURING, 25% EVERGREEN SHRUBS TO BE 30" TALL, 24" SPREAD EVERGREEN, 5' O.C. MIN.

EXISTING VEGETATION MAY BE USED TO MEET TREE BUFFER REQUIREMENT IFON SITE BY THE

LANDECAPE PLANS SHOWING COMPLIANCE WITH THE ZONING ORDINANCE AND CONDITIONAL ZONING PLAN SHALL BE SUBMITTED FOR APPROVAL DURING THE BUILDING PERMIT PROCESS.

DESIGN GUIDELINES:

- A. ARCHITECTURAL TREATMENT
- I THE ARCHITECTURE OF THE DAYCARE BUILDING LOCATED WITHIN THE PARCEL WILL BE RESIDENTIAL IN CHARACTER.
- 2. THE OUTDOOR PLAY SPACE ASSOCIATED WITH THE DAYCARE CENTER WILL BE ENCLOSED WITH A DECORATIVE ALUMINUM FENCE, AND VINYL PICKETS ADJACENT
- 3. ANY DUMPSTER OR TRASH RECEPTACLE "CORRAL" ASSOCIATED WITH THE DAYCARE CENTER WILL BE SCREENED BY A SOLID ENCLOSURE WITH A GATE AND WILL ALSO HAVE A FIVE FOOT (5') MINIMUM PLANTING STRIP AROUND THE
- 4. MAXIMUM AREA OF TOTAL BUILDING PLANS WILL BE 13.000 SF
- 5. THE MAX. BLDG. HT WILL NOT EXCEED 40'-0"
- I. OFF STREET PARKING WILL MEET THE MINIMUM STANDARDS ESTABLISHED UNDER THE ORDINANCE. (32 REQUIRED -- 33 PROVIDED)
- C. STORM WATER MANAGEMENT
 - THE CITY OF CHARLOTTE.
 - A FIVE FOOT (5') SIDEWALK AND AN EIGHT FOOT (8') WIDE PLANTING STRIP WILL BE INSTALLED ALONG MT HOLLY HUNTERSVILLE RD. AND HARWOOD LANE.
 - ALL SIGNS PLACED ON THE SITE WILL BE ERECTED IN ACCORDANCE WITH THE REQUIREMENTS OF THE ORDINANCE.
- I. ALL FREESTANDING LIGHTING FIXTURES INSTALLED WILL BE UNIFORM IN DESIGN AND THE MAXIMUM HEIGHT OF ANY SUCH LIGHTING FIXTURE, INCLUDING ITS BASE, MAY NOT EXCEED FIFTEEN FEET (15') IN HEIGHT.
- ALL DIRECT LIGHTING WITHIN THE SITE (EXCEPT STREETLIGHTS WHICH MAY BE ERECTED ALONG PRIVATE DRIVES AND STREETS) WILL BE CAPPED TO PROJECT LIGHT DOWNWARD AND OTHERWISE DESIGNED SUCH THAT DIRECT ILLUMINATION DOES NOT EXTEND PAST ANY ADJACENT PROPERTY LINE. CONSIDERATION WILL BE GIVEN TO THE IMPACT OF LIGHTING BOTH WITHIN AND WITHOUT THE PERIMETER OF THE SITE. ITEMS FOR CONSIDERATION WILL INCLUDE INTENSITY, CUTOFF ANGLES, COLOR, ENERGY EFFICIENCY, AND SHIELDING SOURCES OF LIGHT, THE INTENT BEING TO ELIMINATE GLARE TOWARDS PUBLIC STREETS AND ADJACENT PROPERTIES. NO "WALL PAK" TYPE LIGHTING WILL BE USED.

- FIRE HYDRANTS SHALL BE LOCATED WITHIN SEVEN HUNDRED FIFTY FEET (150') OF THE MOST REMOTE POINT OF BUILDINGS AS THE TRUCK TRAVELS.
- RIGHT OF WAY DEDICATION ON NORTH SIDE OF HIGHWAY (MT. HOLLY HUNTERSVILLE RDJ 20 OF 50 FT RIGHT OF WAY TO BE CONVEYED TO THE CITY OF CHARLOTE.

INTERNAL TREE REQUIREMENTS

ONE TREE PER 10,000 S.F. OF IMPERVIOUS AREA. ALL PARKING SPACES WITHIN 60 FT. OF A TREE. MINIMUM LANDSCAPE AREA AS A PERCENTAGE OF ENTIRE SITE IS 5% FOR RENOVATED SITES AND 10%

STREET ALIGNMENT NOTES

THE DEVELOPER OF THIS PROPERTY SHALL BE RESPONSIBLE FOR THE FOLLOWING IMPLIED TASKS: I- RECORD A PLAT FOR BOTH PROPERTIES ON EACH SIDE OF THE NEW HARWOOD

2- DEVELOP CITY APPROVED CONSTRUCTION PLANS, WITH NECESSARY PERMITS, FOR THE ROAD ALIGNMENT AND OTHER ROAD IMPROVEMENTS, AS DEPICTED BY SITE PLAN.


3- CONDUCT ALL SITE AND OFF SITE CONSTRUCTION WORK, TO INCLUDE QUALITY

CONTROL AND ASSURANCE, WHICH WILL INCLUDE ROADWAY DEMOLITION, GRADING, INSTALLATION OF CURB, GUTTER, SIDEWALK, PAVING, MARKING AND TRAFFIC CONTROL.

4- PROVIDE A MATERIAL QUANTITY TAKE-OFF, WITH THE EXCEPTION OF ITEMS THAT THE CITY REQUIRES THE DEVELOPER TO BUILD (CURB, GUTTER AND SIDEWALK ALONG SITE FRONTAGE), SUBJECT TO CONSTRUCTION COSTS AND AVAILABILITY OF FUNDING, COOT CAN PROVIDE REIMBURSEMENT TO THE DEVELOPER BASED UPON THE COST OF CITY FORCES DOING THE WORK. 5- DEDICATION OF RIGHT OF WAY TO BE TIED TO THE FIRST C.O. ON THE FIRST

THE PETITIONER SHALL TIE-IN TO THE EXISTING STORM WATER SYSTEM(S). THE PETITIONER SHALL HAVE THE RECEIVING DRAINAGE SYSTEM(S) ANALYZED TO ENSURE THAT IT WILL NOT BE TAKEN OUT OF STANDARD DUE TO THE DEVELOPMENT. IF IT IS FOUND THAT !DEVELOPMENT WILL CAUSE THE STORM DRAINAGE SYSTEM(S) TO BE TAKEN OUT OF STANDRD, THE PETITIONER SHALL PROVIDE ALTERNATE METHODS TO PREVENT THIS FROM OCCURING.

AFFROMED BY CITY COUNCIL



C.L. Helt, Architect Inc.

1136 Greenwood Cliff Charlotte, NC 28204

Ph. 704-342-1686 Fx. 704-343-0054 E-MAIL CHETHELT @ CLHELT.COM

ARCHITECT'S PROJECT #04161

오

ZO PLAI OSE ROF

SP

THIS DRAWING AND ITS COPIES ARE THE COPYRIGHT OF THE ARCHITECT. THEY MAY NOT BE USED FOR PROJECTS OTHER THAN THE DESIGNATED PROJECT WITHOUT THE SPECIFIC WRITTEN APPROVAL OF C. L. HELT ARCHITECT INC., AND OR CHESTER LEROY HELT, ARCHITECT

Drawn By : D. MYERS

Checked By

C.L. HELT

Revisions : 7-14-05 2 7-26-05 8-02-05

Date :

Sheet No.

AUG 0 9 2005