







**1 SOUTH ELEVATION**  
 A201 SCALE: 1/4" = 1'-0" R.E. = 1/1A101

- ### ELEVATION NOTES
- SEE DISCIPLINE SHEETS FOR DISCIPLINE SPECIFIC NOTES
1. ADDRESSING SIGNAGE TO BE LOCATED ON THE SIDE OF THE BUILDING FROM WHERE THE BUILDING IS ADDRESSED (ONE SIDE ONLY). PROVIDE BUILDING ADDRESS IN 8" HIGH LETTERS TO BE APPROVED BY FIRE MARSHALL.
  2. FACE OF SLAB SHALL NOT BE EXPOSED AT SLOPED EXTERIOR PAVING CONDITIONS. COORDINATE EXT. PAVING CONDITIONS WITH CIVIL, TYP.
  3. COORDINATE ALL DOWNSPOUT TIE-INS WITH CIVIL DRAWINGS. PROVIDE SPLASH BLOCKS FOR DOWNSPOUTS W/OUT TIE-INS.
  4. VERTICAL CONTROL JOINTS ARE ILLUSTRATED FOR REFERENCE PURPOSES IN BUILDING ELEVATIONS. C.J.'S ARE RECOMMENDED WHERE TRANSITIONS IN BRICK HEIGHT OCCUR, AT THE CORNERS OF LARGE OPENINGS, ALL INSIDE CORNERS, WITHIN 10' OF OUTSIDE CORNERS AND A MAXIMUM OF 30' O.C. MASONRY CONTRACTOR TO PROVIDE HORIZONTAL AND VERTICAL EXPANSION JOINTS IN BRICKWORK PER TECHNICAL NOTES 18A-AS PUBLISHED BY THE BRICK INDUSTRY ASSOCIATION.
  5. NO MASONRY CORE HOLES SHALL BE EXPOSED, TYP. CLOSURE (SOLID CORE) MASONRY SHALL BE USED WHERE CORE HOLES WOULD OTHERWISE BE EXPOSED TO ELEMENTS.
  6. EXPOSED STEEL LINTELS AND BREAK METAL TO BE PAINTED TO MATCH ADJACENT SURFACE UNLESS OTHERWISE NOTES, TYP.
  7. ALL PENETRATIONS, INCLUDING WINDOWS AND DOORS, SHALL BE SEALED TO THE BACKUP WALL AT THE PRIMARY MOISTURE BARRIER.
  8. ALL CAULKING IS TO MATCH ADJACENT SURFACES.
  9. PROVIDE SOLID BLOCKING WITHIN WALL CAVITY SEGMENTS BEHIND ALL EXTERIOR LIGHTS AND SIGNAGE.

### EXTERIOR COLOR LEGEND

PAINT COLORS TO BE COORDINATED DURING CONSTRUCTION WITH ARCHITECT, OWNER AND HISTORIC LANDMARKS COMMISSION.

---

### EXTERIOR SYMBOL LEGEND

SEE DISCIPLINE SHEETS FOR DISCIPLINE SPECIFIC SYMBOLS

Ⓜ	DOOR TAG	Ⓜ	SPOT ELEVATION MARKERS
Ⓜ	WINDOW TAG (REFER TO A602 FOR WINDOW SIZES AND INFORMATION)	Ⓜ	LEVEL MARKER
D.S.	DOWNSPOUT LOCATION	Ⓜ	CENTER LINE
CJ	CONTROL JOINT LOCATION		

DETAIL SHEET 1/A301 SECTION DETAIL

DETAIL SHEET 1/A301 ENLARGED VIEW

E1-A0 EXTERIOR ASSEMBLY TYPE. SEE A303 FOR ASSEMBLY TYPES

P1 EXTERIOR FINISH COLOR. SEE COLOR LEGEND

**neighboring concepts**  
 ARCHITECTURE ■ PLANNING ■ INTERIORS  
 1635 West Trade Street, Suite 1A  
 Charlotte, North Carolina 28216  
 T:704.374.0916 F:704.342.3808  
 www.neighboringconcepts.com

This drawing and the design shown are the property of Neighboring Concepts, PLLC. The reproduction, copying, or other use of this drawing without their written consent is prohibited and any infringement will be subject to legal action.  
 ©2017 Neighboring Concepts, PLLC

**LandDesign.**  
 223 NORTH GRAHAM STREET  
 CHARLOTTE, NC 28202  
 704.333.0325  
 WWW.LANDDESIGN.COM  
 NC ENGINEERING LICENSE # C-0658




**REZONING PETITION NUMBER 2019-143**

**1024 N. TRYON ST. CHARLOTTE, NC 28217**

No.	Description	Date
1	REZONING SUBMITTAL	09/17/2019
2	REZONING SUBMITTAL	12/12/2019
3	REZONING SUBMITTAL	01/28/2020

BIM 360://1024 North Tryon Street/1024 N Tryon\_Revit 2019\_Central.rvt  
 1/17/2019 5:34:33 PM



**2 EAST ELEVATION**  
 A201 SCALE: 1/4" = 1'-0" R.E. = 1/1A101

**ARCHITECTURAL ELEVATIONS**

ISSUE DATE: January 28, 2020

CHECKED: NLD  
 SHEET BY: MIRO  
 PROJECT NUMBER: LD# 1019346

**RZ-3**



**REZONING PETITION NUMBER 2019-143**

**1024 N. TRYON ST. CHARLOTTE, NC 28217**

No.	Description	Date
1	REZONING SUBMITTAL	09/17/2019
2	REZONING SUBMITTAL	12/12/2019
3	REZONING SUBMITTAL	01/28/2020

**ARCHITECTURAL ELEVATIONS**

ISSUE DATE: January 28, 2020

CHECKED: \_\_\_\_\_

SHEET BY: \_\_\_\_\_

PROJECT NUMBER: LD# 1019346

**RZ-4**

**ELEVATION NOTES**


- SEE DISCIPLINE SHEETS FOR DISCIPLINE SPECIFIC NOTES
- ADDRESSING SIGNAGE TO BE LOCATED ON THE SIDE OF THE BUILDING FROM WHERE THE BUILDING IS ADDRESSED (ONE SIDE ONLY). PROVIDE BUILDING ADDRESS IN 6" HIGH LETTERS TO BE APPROVED BY FIRE MARSHALL.
  - FACE OF SLAB SHALL NOT BE EXPOSED AT SLOPED EXTERIOR PAVING CONDITIONS. COORDINATE EXT. PAVING CONDITIONS WITH CIVIL TYP.
  - COORDINATE ALL DOWNSPOUT TIE-INS WITH CIVIL DRAWINGS. PROVIDE SPLASH BLOCKS FOR DOWNSPOUTS W/OUT TIE-INS.
  - VERTICAL CONTROL JOINTS ARE ILLUSTRATED FOR REFERENCE PURPOSES IN BUILDING ELEVATIONS. CJS ARE RECOMMENDED WHERE TRANSITIONS IN BRICK HEIGHT OCCUR, AT THE CORNERS OF LARGE OPENINGS, ALL INSIDE CORNERS, WITHIN 10' OF OUTSIDE CORNERS AND A MAXIMUM OF 30' O.C. MASONRY CONTRACTOR TO PROVIDE HORIZONTAL AND VERTICAL EXPANSION JOINTS IN BRICKWORK PER TECHNICAL NOTES 18A AS PUBLISHED BY THE BRICK INDUSTRY ASSOCIATION.
  - NO MASONRY CORE HOLES SHALL BE EXPOSED, TYP. CLOSURE (SOLID CORE) MASONRY SHALL BE USED WHERE CORE HOLES WOULD OTHERWISE BE EXPOSED TO ELEMENTS.
  - EXPOSED STEEL LINTELS AND BREAK METAL TO BE PAINTED TO MATCH ADJACENT SURFACE UNLESS OTHERWISE NOTES, TYP.
  - ALL PENETRATIONS, INCLUDING WINDOWS AND DOORS, SHALL BE SEALED TO THE BACKUP WALL AT THE PRIMARY MOISTURE BARRIER.
  - ALL CAULKING IS TO MATCH ADJACENT SURFACES.
  - PROVIDE SOLID BLOCKING WITHIN WALL CAVITY SEGMENTS BEHIND ALL EXTERIOR LIGHTS AND SIGNAGE.

**EXTERIOR COLOR LEGEND**


PAINT COLORS TO BE COORDINATED DURING CONSTRUCTION WITH ARCHITECT, OWNER AND HISTORIC LANDMARKS COMMISSION.

**EXTERIOR SYMBOL LEGEND**

- SEE DISCIPLINE SHEETS FOR DISCIPLINE SPECIFIC SYMBOLS
- 1t DOOR TAG
  - 1t WINDOW TAG (REFER TO A602 FOR WINDOW SIZES AND INFORMATION)
  - D.S. DOWNSPOUT LOCATION
  - C.J. CONTROL JOINT LOCATION
  - SECTION DETAIL
  - ENLARGED VIEW
  - E1-A0 EXTERIOR ASSEMBLY TYPE. SEE A030 FOR ASSEMBLY TYPES
  - P1 EXTERIOR FINISH COLOR. SEE COLOR LEGEND
  - SPOT ELEVATION MARKERS
  - LEVEL MARKER
  - CENTER LINE



**1 NORTH ELEVATION**  
SCALE: 1/4" = 1'-0"  
R.E. = 1/A101



**2 WEST ELEVATION**  
SCALE: 1/4" = 1'-0"  
R.E. = 1/A101